

Customer: City of Davis

Davis OK

Contact: Bert Curtis

Phone:

Fax:

Quote Number: JA1394

Quote Date: 4/29/2021

Quote valid until: 6/13/2021

Customer Ref: D2018552

Salesperson: M Johnson

Prepared By: jargo

QTY	DESCRIPTION
	Chassis Info - Purchased by ETI
1	2019 Chassis
1	CHEVY 6500 CHASSIS 84CA 4x4 Diesel
1	Tri-mode Start Stop Removed from Standard.
	Equipment Technology, LLC Aerial Device ETCMH Series Combination: Articulated / Telescopic Shear Ball Rotation Bearing Emergency lowering valve at bucket Body Harness with Deceleration Lanyard Two Operators and Maintenance Manuals ETC37MH 42' Working Height 37' Ground to Bottom of Bucket 27' 5" Side Reach with End Mount Bucket Continuous Rotation Fiberglass Inner Boom Hoses Inside Boom Are Contained in a Cat Trac 400 lb Bucket Capacity 18 Gallon Oil Reservoir
1	Lower Boom Assembly with Fiberglass Insert for ETC37MH
1	Upper Boom Assy. for ETC37MH.
1	Pedestal (Standard 33.25")
1	End Mount Bucket Bracket with 90 degree Rotator
1	Turret assembly for ETC37MH with pilot-operated hydraulic system.
1	Start/Stop at basket
1	2-Speed Throttle at basket
1	2-Speed chassis integration
1	Emergency Power at basket
1	Switch at lower controls wired to unit options
1	Switch at rear of body wired to unit options. Locate at standard SS position.
1	Hydraulic Jib and Winch Package 1,000 pounds maximum capacity 700 pound minimum capacity Hydraulic Tilting Jib Mounted on Side of Boom Hydraulic Jib Extension Hydraulic Winch Mounted Under Jib 60' x 1/2" Winch Line with Swivel Hook
1	Non-Metallic 4-Function Single-Handle Control with Hydraulic Tool Circuit with flow divider and pressure relief. Pilot-



Equipment Technology, LLC
 341 NW 122nd Street
 Oklahoma City, OK 73114
 Phone: 888-748-3841
 Fax: 405-755-6829
 E-mail: sales@eti1.com

QUOTATION

Quote ID: JA1394

Page 2 of 5

QTY	DESCRIPTION
	operated upper control valve for boom functions.
1	Hose kit for ETC37MH equipped with pilot-operated upper controls and side-mount jib and winch.
1	Powder Paint White with ETI Powder Coating Process
1	Bucket, 24 X 30 Left Step
1	PTO with integrated solenoid, 6-BOLT CHELSEA, 122%, ALLISON 1000-2700, PUMP, 1.40CID, (7.5GPM @1200 RPM) ***REQUIRES PTO OPENING ON TRANSMISSION***
1	2019 Chevrolet diesel exhaust heatshield for right hand PTO.
1	Outrigger Straight & A-Frame A-Frame Outrigger assembly mounted between body and truck cab. Vertical outriggers mounted in rear extension at rear of body. Includes Selector/Outrigger combination valve. The outrigger valves will be mounted inside the outrigger covers. For 34" and above frame heights. 34 1/8" wide frame. Must maintain 17" ground clearance.
1	Pressure sensing interlock for vertical outriggers and interlock for A-frame outriggers with covers.
1	Outrigger down alarm circuit wired to backup alarm for trucks equipped with front and rear outriggers
1	Four DICA polyurethane outrigger pads, 18"X18"X1"
1	Storage brackets for outrigger pads under the front and rear compartments on both sides. For pads up to 18" X 18" X 1" tall.
1	Chevy 4500/5500/6500 Supersprings for rear
1	Two Inclinometers One centered in cab in view of driver One CS rear - right of Triple ID Light
1	Extra Hydraulic filter for Aerial Device (Shipped Loose)
1	ETI Steel Body
1	Side Box - Street Side With stainless steel door rods and hinges. Also with primer in compartments and neoprene seal around doors. Compartment Layout 132G Height=40" Compartment Depth 20" Front Compartment=26.5" Width Next Compartment=26.5" Width Wheel Well Compartment=52" Width Rear Compartment=27" Width Door Doors will have Whale Tail Latches
1	Side Box - Curb Side With stainless steel door rods and hinges. Also with primer in compartments and neoprene seal around doors. Compartment Layout 132H Height=40" Compartment Depth 20" Front Compartment=26.5" Width Next Compartment=26.5" Width Wheel Well Compartment=52" Width Rear Compartment=27" Width Full Length Shelf with Rear Access Door Doors will have Whale Tail Latches
1	Width=96"
1	Integrated Tailshelf Length=36"



Equipment Technology, LLC
341 NW 122nd Street
Oklahoma City, OK 73114
Phone: 888-748-3841
Fax: 405-755-6829
E-mail: sales@eti1.com

QUOTATION

Quote ID: JA1394

Page 3 of 5

QTY	DESCRIPTION
1	56" Floor Width Integrated Unit Mounting and Subframe
1	Wheelwell, street side, blank front and Dodge fuel filler rear (offset for outriggers)
1	Smoothplate Top on Streetside
1	Latch, Whale Tail.
1	Spring loaded door holders for vertical and chains for horizontal doors.
1	Master Lock System with two Push-Pull handles at the rear. ***NOTE*** spring loaded & held in the open position.
1	Wheelwell, curb side, ringed wheel chock holders front and rear (offset for outriggers)
1	Smoothplate Top on Curbside
1	Latch, Whale Tail
1	Spring loaded door holders for vertical and chains for horizontal doors with a rubber bumper under hotstick door.
1	6" yellow recycled composite tailboard with steel mounting brackets for 56" load area.
1	Through box in tailshelf 6" high by 18" long (door on SS tail shelf skirt and on CS in step)
1	Tailshelf 36"-Steel Smoothplate
1	ICC Bumper 90Wx13V-Receiver Tube Class IV rating (10,000lb. MGTW, 1,200lb. tongue)
1	Pintle adapter plate for 2" receiver.
1	Mudflaps installed.
1	Arch Grab Handle on rear of body - Upright pipe is 10.5" ID wide and 27" OD high.
1	12" Aluminum Grab Handle on rear of body on the curbside
1	Smoothplate Entryway Steps in side of 36" Tailshelf on Curbside with gripstrut step underneath.
1	Body Clearance Lights - LED 3/4" Round 2 Red and 2 Amber
1	Reflectors
1	Body Tail Lights - LED (stop/tail/turn) with license/tag light mounted on the SS rear as space allows.
1	Backup Lights - LED
1	Triple ID Lights - LED
1	Paint body standard ETI White (132)
1	Non-Skid on Bumper
1	Non-Skid on Cargo Area Floor and approximately 8" up walls
1	Non-Skid on Cargo Area Walls
1	Non-Skid on Compartment Tops
1	Non-Skid on Tailshelf
1	Boom Support and Bucket Support. Offset for objects in street side load area.
1	No Counterweight Required for Stability
2	SS1-Adjustable Shelf
6	SS1-Dividers, Shelf/Drawer
2	SS2-Adjustable Shelf
6	SS2-Dividers, Shelf/Drawer
1	SS3-Middle Shelf
8	SS3-Dividers, Shelf/Drawer
1	SS4-Adjustable Shelf
3	SS4-Dividers, Shelf/Drawer
2	CS1-Adjustable Shelf



Equipment Technology, LLC
 341 NW 122nd Street
 Oklahoma City, OK 73114
 Phone: 888-748-3841
 Fax: 405-755-6829
 E-mail: sales@eti1.com

QUOTATION

Quote ID: JA1394

Page 4 of 5

QTY	DESCRIPTION
6	CS1-Dividers, Shelf/Drawer
2	CS2-Adjustable Shelf
6	CS2-Dividers, Shelf/Drawer
1	CS3-Blank
1	CS4-Removable Swivel Material Hooks arranged 2-3-2. Each hook has 5 possible fixed positions.
1	Unit Safety Switch - Parking brake must be set before unit will operate
1	Backup Alarm
1	400 Lb Basket Capacity (with outriggers down)
1	6 prong (pole) round trailer socket. ***NOTE INSTALL LOCATION***SS of receiver tube, see build drawing for dimensions.
1	Combination pintle hitch with 2" ball
1	Bucket Cover with foam insert for 24X30 bucket
1	24X30 Bucket Liner-polyethylene
1	Stainless steel grounding lug attached to frame. (Standard location is CS ICC Bumper angled gusset support).
1	One amber strobe light. ***NOTE LOCATION*** SS of HR
1	Supply and Install ETI demo decals.
1	DOT Kit -- 5 LB. ABC fire extinguisher mounted in bottom of SS1. "Fire extinguisher inside" decal placed at the lower right corner on SS1 door. Triangle Warning Kit, Spare fuses for Chevy truck Required per Federal Motor
1	2 Rubber Wheel Chocks, 8.5Wx10.5Lx5.75H
1	Cone Holder installed (Standard location, on SS tailshelf for best fit).
138	Delivery to Destination; F.O.B. Davis, OK
1	DOT inspection
2	Strobe light mounting bracket, outboard on HR each side
2	Go light or Aux light mounting bracket, inboard of strobes
1	Peterson model # 397 LED light for entryway lighting. See build drawing for location.
1	Install Bracket for Chevy or Dodge factory Back-up Camera
1	Unit Control Module for Chevy/International Medium Duty Chassis 4500-6500. Mounted behind seat in cab.
1	Switch inside the cab wired to start/stop. Located on the driver side of the steering wheel.
2	Two ECCO 3510 amber surface mount LED strobe lights. ***NOTE LOCATION*** 2 on front grill and two on tail channel light bar.
1	Rear outrigger cover for ETCMH on steel body. 3/4" indicator lights installed in the outrigger cover.
1	20" Tall headache rack on front of body with flattened expanded metal and gussets at the corner. Space for toolbox on curbside.
1	Switch panel, Whelen # PCC6W,
1	Demo cleaning and touch-up for delivery to customer. Fill fuel tank to full.
1	ETI warranty is two year parts and labor. Lifetime structural warranty on the aerial device so long as the initial purchaser owns the product.

The following options may be added: